

Table Adhesive

General

Water based table adhesive

Advantages

- Table Adhesive is economical than sprays.
- · Suitable to ecological standards.

Applications

- Table Adhesive is used for gluing textile materials to print tables.
- It is designed to strenght for pressure of low noise that is emulsion polymer for ready-touse.
- It provides excellent adhesion even if in high application speed.
- Table Adhesive has improved drying properties which are peeling, adhesion and cutting.

Usage

- It sprays to application tables with special air spray aparatus.
- It has low water strenght therefore Table
 Adhesive can be used with warehouse labels
 that should be designed as hard and/or
 plastise (made from PVC, PE and PP film)
- Before use please stir this product well.
- Filtration should be advised with low power pump (>50µ)

Storage & Shelf Life

- Keep containers dry and tightly closed. Store in a ventilated place between (+5)-(+30)°C /(+41)-(+86)°F of temperature.
- It should be consumed within 2 years after the production date.



Technical Details



Appearance Liquid



Odor Characteristic



Color Milky



Viscosity

Max. 600 (mPa.s)



Density

1,15 g/cm3 (77 °F/25°C)



Specific Gravity

Appr. 1,1 g/cm³



7,0 - 8,0



Boiling Point >100°C (212°F)



Solubility

Dispersible in water



Explosion Hazard

It is not explosive



Packaging Information

Table Adhesive is packed in 5/10/20/30/60 kg blue plastic cans

Important

The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. When any help or assistance is required, our technical department is ready for help.

In case of emergency, Safety Data Sheet of this product should be ready for help at the working area. The warnings are given on safety data sheet of this product is for use outside the manufacturer/ distributor to direct/indirect can not be held responsible for any loss or damage.

Rev. DATE: 1 December 2021 Rev. No: 02