



GW 10 Clear

General

GW 10 Clear is a water based printing base used to achieve an elastic and soft touching effect in textile printing. It can be blended with any water based pigment.

Advantages

- If used correctly as advised, the dry-wet rubbing and washing fastness are high.
- It is non-clogging high performance clear for high number mesh.
- It provides elastic and soft-handfeel clear for open mesh.
- It is fixed at (140°C/ 150°C), 2 2,5 mins; (160°C / 170°C), 1,5
 2 mins.
- Suitable for CMYK Printing.
- Rubbing and washing tests should be applied 24 hours after curing.

Applications

- GW 10 Clear has been manufactured for elastic and proper surface printings.
- Never use water to reduce the viscosity.
- Before use, please stir the product well. Do not use any additives that are not advised.
- After using, the screen should be cleaned with the water and sponge.

Usage

- It provides to print with the silk-screen that are made between 55-120 mesh.
- 60 70 Shore, U type dr blade should be used.
- It can be mixed with GW 20 White in any ratio.

Storage & Shelf Life

- Keep containers dry and tightly closed. Store in a ventilated place between (+5)-(+30) °C/(+41)-(+86) °F of temperature.
- It should be consumed within 2 years after the production date.

Technical Details:

Appearance
Transparent Paste

Odor
Characteristic

Color
Yellowish

Viscosity [(77°F/25°C) sp: 6, rpm: 10 Brookfield]: 75.000 - 95.000 [mPa.s]

Density 1,06 g/cm3 (77 °F / 25 °C)

Specific Gravity

7.3-8.3

Boiling Point

рH

>100°C (212°F) ------Solubility

Soluble in water

Explosion Hazard It is not explosive

Packaging Information GW 10 Clear is packed in

5/10/20/30/60 Kg blue polyethylene cans.

Important

The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. When any help or assistance is required, our technical department is ready for help.

In case of emergency, Safety Data Sheet of this product should be ready for help at the working area. The warnings are given on safety data sheet of this product is for use outside the manufacturer/ distributor to direct/indirect can not be held responsible for any loss or damage.

Rev. DATE: 16 September 2021

Rev. No: 01

TDS No: 202 **Page** 1 / 1