

VP 10 Clear

General

VP 10 Clear is a polyurethane based printing used to achieve an elastic and soft touching effect in textile printing.

It can be used as a transparent or can be colored with pigments.

Advantages

- If used correctly as advised, the dry-wet rubbing and washing fastness are high.
- It provides elastic and soft-handfeel clear for open mesh.
- High working performance
- Non-clogging Chemical content maintains continuous machine run.
- It is fixed at (160°C - 170°C) , 1,5 - 2 mins ; (140°C - 150°C) , 2- 2,5 mins.
- Suitable to ecological standards.
- Rubbing and washing tests should be applied 24 hours after curing.

Applications

- VP 10 Clear has been manufactured for elastic and proper surface printings.
- Never use water to reduce the viscosity.
- Before use, please stir the product well.
- Do not use any additives that are not advised.
- After using, the screen should be cleaned with the water and sponge.

Usage

- It provides to print with the silk-screen that are made between 62-77 mesh.
- 60 - 70 Shore, U type should be used.
- It can be mixed with VP 20 White in any ratio.

Storage & Shelf Life

- Keep containers dry and tightly closed. Store in a ventilated place between (+5)-(+30)°C /(+41)-(+86)°F of temperature.
- It should be consumed within 2 years after the production date.

Important

The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. When any help or assistance is required, our technical department is ready for help.

In case of emergency, Safety Data Sheet of this product should be ready for help at the working area. The warnings are given on safety data sheet of this product is for use outside the manufacturer/ distributor to direct/indirect can not be held responsible for any loss or damage.



TECHNICAL DATA SHEET

Technical Details



Appearance

Transparent Paste



Odor

Characteristic



Color

Yellowish



Viscosity

[(77°F/25°C) sp: 7, rpm: 20 Brookfield] :
70.000 - 80.000 [mPa.s]



Density

1,05 g/cm³ (77°F/25°C)



pH

7,8 - 8,5



Boiling Point

>100°C (212°F)



Solubility

Soluble in water



Explosion Hazard

It is not explosive



Packaging Information

VP 10 Clear is packed in
5/10/20/30/60 kg blue polyethylene
cans.